

Doporučené rozteče D170

pro plexisklo opál LT 30%

(LED opál LT 50%) + bannerová backlit fólie starflex

vysoká svítivost

střední svítivost

slabší svítivost

D170-1		
Hloubka	Osová rozteč v mm	lm/m ²
30 mm	60 × 60	17 000
40 mm	80 × 80	9 563
50 mm	100 × 100	6 120
60 mm	110 × 110	5 058
70 mm	120 × 120	4 250
80 mm	135 × 135	3 358

D170-2		
Hloubka	Osová rozteč v mm	lm/m ²
70 mm	110 × 160	6 955
80 mm	120 × 170	6 000
90 mm	130 × 180	5 231
100 mm	140 × 190	4 602
110 mm	150 × 200	4 080
120 mm	160 × 210	3 643

D170-3		
Hloubka	Osová rozteč v mm	lm/m ²
120 mm	150 × 210	5 829
130 mm	160 × 220	5 216
140 mm	170 × 230	4 696
150 mm	180 × 240	4 250
160 mm	190 × 250	3 865
170 mm	200 × 260	3 531
180 mm	200 × 260	3 531
190 mm	200 × 260	3 531
200 mm	200 × 260	3 531

D170-4		
Hloubka	Osová rozteč v mm	lm/m ²
150 mm	190 × 290	4 443
160 mm	200 × 300	4 080
170 mm	170 × 310	3 760
180 mm	210 × 310	3 477
190 mm	210 × 310	3 477
200 mm	210 × 310	3 477
210 mm	210 × 310	3 477
220 mm	210 × 310	3 477
230 mm	210 × 310	3 477
240 mm	210 × 310	3 477
250 mm	210 × 310	3 477