

Technical data

CODE:


54413

PRODUCT:

LED STRIPS

NOTE:

TECHNICAL DATA

IMAGE:**LAST UPDATE:**

9/2021

LED STRIPS


CE	RoHS	DC 12V	12 W	60 LEDs	10 mm	3 years	20 IP
-----------	-------------	---------------	-------------	----------------	--------------	----------------	--------------

Model 54413



Features:

- 2835 LED
- 5 SDCM, one Bin only
- 80 CRI
- 35 000 Hour life
- 3M adhesive backing tape
- CE, RoHS, UL approved



Model	54413
Input voltage	12 Vdc
Input current	1,0A/1m & 5,0A/5mts
Power	Typ. 12W/m & max. 60W/5mts
Lumens /m	1 400Lm@6 000K
CRI	80
Beam angle	120°
Cutting unit	B = 50 mm/3 LEDs
Dimension	A = 16,67 mm; C = 10 mm; D = 1,3 mm
Copper foil	3 ounce
Dimmable	PWM & 1-10V
Temperature range	-25°C ~ 55°C / -13°F ~ 131°F
Energy efficiency class	F


Notes:

- The given data are typical value, due to tolerances of the production process and electrical components, values for light output can be $\pm 10\%$ and electrical power can be $\pm 10\%$. Measurement uncertainty $\pm 5\%$. Values given for 1 m LED strips.
- If the electrical power more than 16W max./m must be used the heat sinking.

Color temperature (Kelvin)



Packing info



5 mts/ roll 250 mts/ carton G. W: 7,0 kgs
 Carton size: 45 x 25 x 26 cm CBM 0,0323

--	--	--	--	--